

TGFU.R21182 - Roofing Systems

Note: We are enhancing our systems and you may notice duplicate entries/missing/outdated data. During this interim period, please contact our Customer Service at <https://www.ul.com/about/locations>.

Roofing Systems

[See General Information for Roofing Systems](#)

ASC BUILDING PRODUCTS, DIV OF ASC PROFILES L L C

R21182

2110 ENTERPRISE BLVD
WEST SACRAMENTO, CA 95691 USA

OTHER SYSTEMS

Class A

Coated steel panels (surfacing) identified as "Skyline Roofing", "Skyline Roofing HP", "Design Span HP", "Nor-Clad", "Strata Rib", "Delta Rib", "Delta Rib III", "Super-Span", "PBR" and "2-1/2 Corrugated".

One or more layers of GAF "VersaShield Underlayment", mechanically fastened, may be used in lieu of the Barrier Board in all combustible Classifications with steel panels.

1. **Deck:** C-15/32

Incline: Unlimited

Impact: Class 4

Barrier Board: — 1/4 in. min. Georgia-Pacific Gypsum LLC "DensDeck® Roofboard" or "DensDeck Prime® Roofboard" or 1/4 in. min United States Gypsum Co. SECUROCK® Glass-Mat Roof Board (Type SGMRX), National Gypsum "DEXcell Glass Mat Roof Board" or "DEXcell FV Glass Mat Roof Board" with all joints staggered a min of 6 in. from the plywood joints.

Ply Sheet (Optional): — Any UL Classified Type G1, G2 or G3 base/ply sheet, Type 15, 20 or 30 felt or UL Classified Prepared Roofing Accessory (TGDY) or "AEP Span Underlayment HT".

Surfacing: — Coated Steel roofing panels, mechanically fastened or with steel screws when roof deck fasteners (panel clips) not required.

2. **Deck:** NC

Incline: Unlimited

Impact: Class 4

Barrier Board: — 1/4 in. min. Georgia-Pacific Gypsum LLC "DensDeck® Roofboard" or "DensDeck Prime® Roofboard" or 1/4 in. min United States Gypsum Co. SECUROCK® Glass-Mat Roof Board (Type SGMRX), National Gypsum "DEXcell Glass Mat Roof Board" or "DEXcell FV Glass Mat Roof Board".

Ply Sheet (Optional): — Any UL Classified Type G1, G2 or G3 base/ply sheet, Type 15, 20 or 30 felt or UL Classified Prepared Roofing Accessory (TGDY) or "AEP Span Underlayment HT".

Surfacing: — Coated Steel roofing panels, mechanically fastened or with steel screws when roof deck fasteners (panel clips) not required.

3. **Deck:** NC

Incline: Unlimited

Impact: Class 4

Barrier Board: — 7/16 OSB or 5/8 in. plywood over polyisocyanurate insulation board or polyisocyanurate composite board, any thickness.

Ply Sheet (Optional): — Any UL Classified Type G1, G2 or G3 base/ply sheet, Type 15, 20 or 30 felt or UL Classified Prepared Roofing Accessory (TGDY) or "AEP Span Underlayment HT".

Surfacing: — Coated Steel roofing panels, mechanically fastened or with steel screws when roof deck fasteners (panel clips) not required.

4. **Deck:** NC

Incline: Unlimited

Impact: Class 4

Insulation: — Polyisocyanurate, glass fiber, perlite or wood fiber, any thickness.

Ply Sheet (Optional): — Any UL Classified Type G1, G2 or G3 base/ply sheet, Type 15, 20 or 30 felt or UL Classified Prepared Roofing Accessory (TGDY) or "AEP Span Underlayment HT".

Surfacing: — Coated Steel roofing panels, mechanically fastened or with steel screws when roof deck fasteners (panel clips) not required.

5. **Deck:** NC

Incline: Unlimited

Impact: Class 4

Insulation: — None required, however any UL Classified insulations may be used over open purlin spans. Any combination and any total thickness of insulation may be used.

Surfacing: — Coated Steel roofing panels, mechanically fastened or with steel screws when roof deck fasteners (panel clips) not required.

6. **Deck:** C-15/32

Incline: Unlimited

Impact: Class 4

Barrier Board: — 1/4 in. min. Georgia-Pacific Gypsum LLC "DensDeck® Roofboard" or "DensDeck Prime® Roofboard" or 1/4 in. min United States Gypsum Co. SECUROCK® Glass-Mat Roof Board (Type SGMRX), National Gypsum "DEXcell Glass Mat Roof Board" or "DEXcell FV Glass Mat Roof Board" with all joints staggered a min of 6 in. from the plywood joints.

Ply Sheet (Optional): — Any UL Classified Type G1, G2 or G3 base/ply sheet, Type 15, 20 or 30 felt or UL Classified Prepared Roofing Accessory (TGDY) or "AEP Span Underlayment HT".

Surfacing: — Coated Steel roofing panels, mechanically fastened or with steel screws when roof deck fasteners (panel clips) not required.

7. **Deck:** C-15/32

Incline: Unlimited

Impact: Class 4

Underlayment: — One or more plies Firestone Building Products LLC "CLAD-GARD SA-FR" self-adhered underlayment.

Ply Sheet (Optional): — One ply Type 30 base sheet or Firestone Building Products LLC "CLAD-GARD SA-FR" self-adhered underlayment.

Surfacing: — Coated steel roofing panels, mechanically fastened or with steel screws when roof deck fasteners (panel clips) not required.

Last Updated on 2020-04-24

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"