Trims and Flashings Guide



Design S	Span hp 📕	Skyline Roofing		
AL41 Angle Cleat	B41 Drip Flashing	B16 Base Trim	C16 C Trim	
2-3/8"	5-1/2" 6"2"	3"	3" 	
CF41 Counter Flashing	G41 Gable	E16 Narrow Eave	E17 Wide Eave	
3-1/2" 1"	1-1/2" 1-1/4" 1/2" 5-7/8" 3/4"	2" 1-1/8" 1/2"	4" 3" 5/8"	
Z42 Closure	OL41 Offset Cleat	E18 Snow Eave	E19 Notched Eave	
	1-1/2" 5/16" 13/16"	5-1/8" 1-3/4" 1-3/4" 1/2"	3-1/4" Varies No customs Pitch Required available	
R41 Ridge	R42 Vented Ridge	E21 Nosed Eave	E22 Nosed Eave	
8-1/2" Pitch Required	9" 1-1/2" 3" Pitch Required	3-3/4" 1-1/2" 1-1/4" 5/8"	3-3/4" 1" 1-1/4" 5/8" Pitch Required	
SF41 Support Flashing	TR41 Transition (High-Low)	EW16 Endwall	EW17 Vented Endwall	
1" 1-3/4" 5-1/4"	7" 16-1/2" Pitch Required	4" 5" Pitch Required	4" 6-3/4" 1-1/8" 1-7/8" Pitch Required	
TR43 Transition (Low-High)	V41 Valley	G5 Adjustable Gable	G16 Narrow Gable	
16-1/2" 7" Pitch Required	1/2" 1" 19-1/2" Pitch Required	6" 4" [1/2"	1/2" 1" 1" 1" 1/2"	
ZL41 "Z" Clip	Z41 "Z" Closure	G17 Standard Gable	G18 Chalet Gable	
2 1/8" 1-3/4" 2" Length 2 1/8"	2-1/8" 1-3/4" 2-1/8"	4" 1/2"	3/4" 3-7/8" 5/8" 6"	





Trims and Flashings Guide

PF16 Peak Flashing PF18			Nu-Wave® Corrugated		
	Vented Peak R16 Hi	p/Ridge	R17 Vented Ridge	R18 Narrow Ridge	
Varies Varies 1/2" Pitch Required	Varies 1-1/8" 2" Pitch Required Pitch Required	5-1/2"	6-3/4" 1-1/8" Required		
SS1 Starter Strip SW16 Sidev	vall SW17 Sidewall	SW18 Sidewall	TR16 Transition (Hig	h-Low) TR17 Transition (Low-High)	
2-1/2" 4" 2-1/4" 1-1/8"	<u>3/4"</u> <u>2-1/4"</u> <u>2-1/8"</u> <u>3/4"</u>	4" 2-1/4" 1" 2-1/2"	5" Pitch Required	Varies 5" Pitch Required	
V16 Valley	Z17 Solid Zee Closure	Z18 P	erforated Zee	B1 Base Trim	
1" 12" Pitch Required	2-13/16" <u>1-3/16"</u> Colors may vary 1" Pitch Required	1-3/16" 1" 1" Pitch Required	Varies	2-1/8"	
C13 C-Metal	G19 Gable	IC2 II	nside Corner	OC2 Outside Corner	
3-1/2" 1" 1"	3-1/2" 1/2" 4-3/4" 3/4"	3-1/2"		3-1/2"	
SW8 Sidewall	E6 Eave	EW	/6 Endwall	R8 Ridge	
5-1/4"	5-3/4" 4" 3/4"	4-1/2" Pitch Required	6"	10" Pitch Required	
V6 W-Valley	B6 Drip Edge	C	6 C-Metal	G8 Gable	
3/4" 20-3/4" Pitch Required	4-1/8" <u>1-5/8</u> " 3/4"	1-3/8" 1-1/4"	3-7/8" D	4-7/8" 1-3/4" 5-1/4" 3/4"	
G9 Sculptured Gable	IC7 Inside Corner	0C7 0	utside Corner	SW7 Sidewall	
<u>1"</u> 2-1/8" 5/8" <u>1-1/2"</u> 3-1/2" <u>2-1/8"</u>	4-1/4" 1-3/4" 3/4"		4-3/16" 1-15/16" 5/8"	5-5/8" <u>5"</u> 2-1/8" <u>1"</u>	

ASC BUILDING PRODUCTS

Trims and Flashings Guide

Strata Rib	Nor-Clad	Delta Rib III	I Delta I	Rib 2½ Co	orrugated
B1 Base Trim	C1 7/8" C-Metal	E1 Eave	E2 Eave	E3 Eave	E4 Eave
2-1/8"	2" 7/8"	1-1/2" 3" 1/2"	2" 4-3/8" 1/2"	1-3/8" 1-3/8" 1-3/8" 1/2"	2" 2" 1/2"
3" 3" 1/2"	2" 3-3/8" 1/2"	Ch Required	EW1 Endwall 4" 1/2" 2" 1/2" 3/4"	EW2 Residential Endw	EW17 Vented Endwall 4" 6-3/4" 1-1/8"
G1 Gable	G3 Gable 4" 2-3/4" 1/2"	G4 Residentia	5/8" 3/4"	Chalet Gable 1-5/8" 6" /8"	UC1 Inside Corner
IC2 Inside Corner	OC1 Outside Corner 	OC2 Outside Corner	r PB3 Pitch Break	6" PB4	Pitch Break (Low-High)
PF2 Peak Flash Varies 1/2"	Varies 3/8" Varies 1/2" Pitch Required	Vented Peak Varies 1-1/8" 1-7/8"	R1 Ridge 2" 1/2"	2-1/8" 1-7/8" 13/16"	R2 Vented Ridge 6-3/4" 1-1/8"
R3 Standard R	7"	Residential Ridge 3-3/4" 3-1/2"	5W1 Sid 4" 1-1/8" 2"	lewall S	W2 Residential Sidewall
TC1 Single Track Cove 1-1/2" 3-13/16" 1-7/16 3-13/16"	1-1/2"	1-1/2" 2-1/2" 7-3/16	1"	Valley	V2 Residential Valley

Customer Service Centers Salem, OR: 503-390-7174 or 800-272-7023 | Spokane, WA: 509-536-4097 or 800-776-8771 PS328 0225 web

www.ascbp.com