

Trims and Flashings Guide

Refer to the color key for the most common trims and flashings available by product.

Design Span hp ■

Skyline Roofing ■

<p>L41 Closure</p>	<p>OL41 Offset Cleat</p>	<p>R16 Hip/Ridge</p> <p>Pitch Required</p>	<p>R18 Narrow Ridge</p> <p>Pitch Required</p>
<p>AL41 Angle Cleat</p>	<p>ZL41 "Z" Clip</p>	<p>R17 Vented Ridge</p> <p>Pitch Required</p>	<p>Z16 Perforated Zee</p> <p>Pitch Required</p>
<p>Z41 "Z" Closure</p>	<p>R41 Ridge</p> <p>Pitch Required</p>	<p>Z17 Solid Zee Closure</p> <p>Pitch Required</p>	<p>G16 Narrow Gable</p>
<p>R42 Vented Ridge</p> <p>Pitch Required</p>	<p>V41 Valley</p> <p>Pitch Required</p>	<p>G17 Standard Gable</p>	<p>G18 Chalet Gable</p>
<p>G41 Gable</p>	<p>SF41 Support Flashing</p>	<p>V16 Valley</p> <p>Pitch Required</p>	<p>E16 Narrow Eave</p> <p>Pitch Required</p>
<p>CF41 Counter Flashing</p>	<p>B41 Drip Flashing</p>	<p>E17 Wide Eave</p> <p>Pitch Required</p>	<p>E18 Snow Eave</p> <p>Pitch Required</p>
<p>TR41 Transition (High-Low)</p> <p>Pitch Required</p>	<p>TR43 Transition (Low-High)</p> <p>Pitch Required</p>	<p>E19 Notched Eave</p> <p>No customs available</p> <p>Pitch Required</p>	<p>TR16 Transition (High-Low)</p> <p>Pitch Required</p>

Trims and Flashings Guide

Refer to the color key for the most common trims and flashings available by product.

Skyline Roofing ■ Nu-Wave Corrugated ■ PBR Panel ■

TR17 Transition (Low-High)	SW16 Sidewall	SW17 Sidewall	SW18 Sidewall
<p>Pitch Required</p>			
EW16 Endwall	EW17 Vented Endwall	B16 Base Trim	PF16 Peak Flashing
<p>Pitch Required</p>	<p>Pitch Required</p>		<p>Pitch Required</p>
C13 C-Metal	EW6 Universal Endwall	SW7 Sidewall	G8 Gable
	<p>Pitch Required</p>		
G19 Gable	V6 W-Valley	OC7 Outside Corner	IC7 Inside Corner
	<p>Not available for PBR Panel</p> <p>Pitch Required</p>		
IC11 Universal Inside Corner	R8 Ridge	C6 C-Metal	G9 Sculptured Gable
	<p>Pitch Required</p>		
OC11 Universal Outside Corner	E6 Eave		
	<p>Pitch Required</p>		
SW8 Sidewall	B6 Drip Edge		

Pitch Required = Trim manufactured based on roof pitch. Please ensure roof pitch provided at time of order entry.

Trims and Flashings Guide

Refer to the color key for the most common trims and flashings available by product.

Strata Rib ■ Nor-Clad ■ Delta Rib III ■ Delta Rib ■ 2½ Corrugated ■

R1 Universal Ridge Pitch Required	R3 Standard Ridge Pitch Required	R4 Residential Ridge Pitch Required	R2 Vented Ridge Pitch Required	
C1 7/8" C-Metal Pitch Required	V1 W-Valley Pitch Required	V2 Residential Valley Pitch Required	B1 Base Trim Pitch Required	
E1 Eave Pitch Required	E2 Eave Pitch Required	E3 Eave Pitch Required	E4 Eave Pitch Required	E5 Eave Pitch Required
ER1 Residential 3" Eave Pitch Required	ER2 Residential 4" Eave Pitch Required	G1 Gable Pitch Required	G3 Gable Pitch Required	G4 Residential Gable Pitch Required
PF2 Peak Flashing Pitch Required	OC1 4" x 4" Outside Corner Pitch Required	OC2 Universal Outside Corner Pitch Required	IC1 4" x 4" Inside Corner Pitch Required	
IC2 Universal Inside Corner Pitch Required	SW1 Universal Sidewall Pitch Required	SW2 Residential Sidewall Pitch Required	EW1 Universal Endwall Pitch Required	
EW2 Residential Endwall Pitch Required	PB3 Pitch Break (High-Low) Pitch Required	PB4 Pitch Break (Low-High) Pitch Required	SB1 Snow Break Works with most panels	

Customer Service Centers

Salem, OR: 503-390-7174 or 800-272-7023 | Spokane, WA: 509-536-4097 or 800-776-8771